



DETECTABLE WARNING PATTERN DETAIL



DETECTABLE WARNING PATTERN AREA SHALL BE YELLOW, AND PERPENDICULAR TO THE LONG AXIS OF THE RAMP.

PLAN



	MIN.	MAX.
Α	1 5/8"	2 3/8"
В	5/8"	1 1/2"
С	7/16"	3/4"
D	7/8"	1 7/16"

ELEVATION

TRUNCATED DOMES-SEE NOTE 3

NOTES:

- INSTALL WHEELCHAIR RAMP AS LOCATED ON APPROVED PLANS OR AS DIRECTED BY THE TRAFFIC ENGINEER.
- 2. SEE SD310B FOR CURB RAMP LAYOUT.
- 3. DETECTABLE WARNING PATTERNS MAY BE CREATED BY METHODS THAT WILL ACHIEVE THE TRUNCATED DOME DIMENSIONS, COLOR AND SPACING SHOWN AS DIRECTED BY THE PLANS OR THE TRAFFIC ENGINEER.
- 4. REFER TO WSDOT SIDEWALK RAMP STANDARD PLANS AS DIRECTED BY THE TRAFFIC ENGINEER FOR ALTERNATE HORIZONTAL CURB RAMP DETAILS.

CITY OF REDMOND, WASHINGTON

APPROVED BY: RON GRANT

CITY ENGINEER

REVISION DATE: MARCH 01, 2010





STANDARD DETAILS

SIDEWALK RAMP TYPE 2

FILE NAME: SD310A.DWG DETAIL NUMBER: **310A**